Steel Wire Reinforced Steam 210°C

OIL RESISTANT COVER-ISO 6134-2B

SSW564

ID		OD	WP		BP		BR/r	W	L
inch	mm	mm	bar	psi	bar	psi	mm	g/m	m
1/2"	12.7	25	18	261	180	2610	130	560	40-61
5/8"	16	30	18	261	180	2610	160	780	40-61
3/4"	19	33	18	261	180	2610	190	815	40-61
1"	25.4	40	18	261	180	2610	250	1070	40-61
1 1/4"	32	48	18	261	180	2610	320	1490	40-61
1 1/2"	38	54	18	261	180	2610	380	1865	40-61
2"	50.8	69	18	261	180	2610	500	2695	40-61
2 1/2"	63.5	81	18	261	180	2610	630	3205	40-61
3"	76.2	94	18	261	180	2610	750	4175	40-61
4"	101.6	122	18	261	180	2610	1000	6425	40-61

TÜP : EPM KAUÇUK, DOYMUŞ BUHARA DAYANIKLIDIR.
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ ÇELİK TEL KORDOLAR.
KAPAK : AŞINMAYA, ISIYA, BUHARA, YAĞA, OZONA VE HAVA ŞARTLARINA DAYANIKLI, PİM DELİ ÖZEL SENTETİK KAUÇUK.
UYGULAMA : KİMYA TESİSLERİ, ÇELİK FABRİKALARI, RAFİNERİLER, TERSANELER VE TÜM ENDÜSTRİLERDE MAKSİMUM 18 BAR (261 PSI) ÇALIŞMA BASINCINDA DOYMUŞ BUHAR HİZMETLERİ İÇİN.

TUBE : EPM RUBBER, RESISTANT TO SATURATED STEAM.
REINFORCEMENT : HIGH TENSILE STEEL WIRE CORDS.
COVER : ABRASION, HEAT, STEAM, OIL, OZONE AND WEATHER RESISTANT, PIN-PRICKED SPECIAL SYNTHETIC RUBBER.
APPLICATION : FOR SATURATED STEAM SERVICES AT A MAXIMUM WORKING PRESSURE OF 18 BARS (261 PSI) IN CHEMICAL PLANTS, STEEL MILLS, REFINERIES, SHIPYARDS AND ALL INDUSTRIES.

SEELE : EPM GUMMI, SATTDAMPFBESTIINDIG.
EINLAGE : HOCHZUGFESTE STAHLKORDEINLAGE.
DECKE : ABRIEBFEST, HITZE, DAMPF, ÖL, OZON - UNO WITTERUNGSBESTIINDIG, SPEZIELL GEPRICKTER SYNTHETISCHER GUMMI.
ANWENDUNG : GEEIGNET FÜR ANWENDUNGEN MIT SATTDAMPF MIT MAX. 18 BAR (261 PSI) FÜR CHEMIEINDUSTRIE, STAHLWERKE, RAFFINERIEN, WERFTEN UNO ALLEN INDUSTRIEBEREICHEN.

-40˚C / +210˚C INTERMITTENT TO 232 ˚C
-40˚F / +410˚F INTERMITTENT TO 450 ˚F

İŞARETLEME / MARKING / BESCHRIFTUNG : TRANSFER TAPE OR EMBOSSED

GEYSER - 2B STEAM HOSE - TS EN ISO 6134 - 2B - W.P. 18 Bar (261 PSI) - 210 °C - M

Normlar **Norms** **Normen**	TS EN ISO 6134 TYPE 2- CLASS B ISO 1307	**Renk** **Colour** **Farben**	