ARB495

Aircraft Refueling

EN 1361 Type B

AERO-B Serisi / AERO-B Series

ID		OD	WP		BP		BR/r	W	L
inch	mm	mm	bar	psi	bar	psi	mm	g/m	m
3/4"	19	29	20	290	80	1160	113	522	40-46-61
1"	25.4	38	20	290	80	1160	150	842	40-46-61
1 1/4"	32	45	20	290	80	1160	190	1003	40-46-61
1 1/2"	38	51	20	290	80	1160	225	1162	40-46-61
2"	50.8	65	20	290	80	1160	275	1699	40-46-61
2 1/2"	63.5	79	20	290	80	1160	300	2063	40-46-61
3"	76.2	92	20	290	80	1160	300	2562	40-46-61
4"	101.6	120	20	290	80	1160	450	3734	40-46-61

TÜP : HAVACILIK BENZİNİ VE JET YAKITLARINA DAYANIKLI, İLETKEN NBR KAUÇUK
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL VE 2 ADET ANTİSTATİK BAKIR TEL.
KAPAK : AŞINMAYA, OZONA, HAVA ŞARTLARINA, ISIYA VE YAĞA DAYANIKLI ÖZEL SENTETİK KAUÇUK
UYGULAMA : % 30'A KADAR AROMATİK İÇERİĞİ OLAN UÇAKLARIN YERDE YAKIT İKMALİ İÇİN.

TUBE : AVIATION GASOLINES AND JET FUELS RESISTANT,CONDUCTIVE NBR RUBBER
REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE AND 2 ANTISTATIC COPPER WIRE.
COVER : ABRASION, OZONE, WEATHER, HEAT AND OIL RESISTANT SPECIAL SYNTHETIC RUBBER
APPLICATION : FOR THE GROUND REFUELLING OF AIRCRAFTS HAVING AN AROMATIC CONTENT UP TO 30 %.

SEELE : FLUGZEUG- UND JETKRAFTSTOFFBESTANDIG, ISOLIEREND, NBR GUMMI, SCHWARZ.
EINLAGE : HOCHZUGSFESTE SYNTETISCHE TEXTILEINLAGE UND 2 ANTISTATISCHER KUPFERLITZE ZUR BESSEREN LEITFAHIGKEIT.
DECKE : ABRIEBFEST, OZON-,WETTER-,HITZE-,UND ÖLBESTANDIG, SPEZIELLER SYNTHETIKGUMMI.
ANWENDUNG : ZUR FLUGZEUGBETANKUNG AM BODEN, MIT 30% MAX. AROMATENANTEIL.

-30°C /+ 65°C
-22°F /+149°F

İŞARETLEME / MARKING / BESCHRIFTUNG : **TRANSFER TAPE OR EMBOSSED**

AERO - B AIRCRAFT REFUELING HOSE • TS EN 1361 TYPE B • M • W.P. 20 BAR (290 PSI)

Normlar Norms Normen	EN ISO 1825 TYPE-B TS EN 1361 TYPE - B TS EN iso 1825 TYPE-B	Renk Colour Farben	