ABFC849

WHITE SDC Serisi / WHITE SDC Series

ID	OD	WP	BP	VACUUM	BR/r	W	L
inch	mm	mm	bar	psi	bar	psi	bar	mm	g/m	m
1"	25,4	37,5	10	145	30	435	-0,92	60	805	40-46-61
1 1/4"	32	44	10	145	30	435	-0,92	75	975	40-46-61
1 1/2"	38	51	10	145	30	435	-0,92	90	1294	40-46-61
2"	50,8	64,5	10	145	30	435	-0,92	125	1779	40-46-61
2 1/2"	63,5	77,5	10	145	30	435	-0,92	175	2387	40-46-61
3"	76,2	90,5	10	145	30	435	-0,92	200	3080	40-46-61
3 1/2"	90	106	10	145	30	435	-0,92	250	3860	40-46-61
4"	101,6	119	10	145	30	435	-0,92	275	4660	40-46-61
5"	127	147	10	145	30	435	-0,92	350	6830	40-46-61
6"	152,4	173	10	145	30	435	-0,92	400	8960	40-46-61
8"	203,2	227	10	145	30	435	-0,80	750	14090	30
10"	254	279	10	145	30	435	-0,80	1100	17310	20

Aşınma Kaybı Değeri: Acc DIN 53516 ≤ 120 mm3
Abrasion Loss Value: Acc DIN 53516 ≤ 120 mm3
Abriebwert nach DIN 53516 ≤ 120 mm3

TÜP : BEYAZ RENKLİ, TOKSİK OLMAYAN, AŞINMAYA DAYANIKLI DOĞAL KAUÇUK.
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL, ÇELİK TEL HELİS VE ANTİSTATİK BAKIR TEL.
KAPAK : AŞINMAYA, OZONA VE HAVA ŞARTLARINA DAYANIKLI PİM DELİKLİ ÖZEL SENTETİK KAUÇUK.
UYGULAMA : DÖNME AŞINDIRICI ÜRÜNLERİN EMME VE TAHLİYESİ İÇİN. (GENERALİKSİT TOZLUGRANÜL VB.)

TUBE : WHITE COLOUR, NON- TOXIC, ABRASION RESISTANT NATURAL RUBBER.
REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE, STEEL WIRE HELIX AND ANTISTATIC COPPER WIRE.
COVER : ABRASION, OZONE AND WEATHER RESISTANT PIN-PROKED, SPECIAL SYNTHETIC RUBBER.
APPLICATION : FOR SUCTION AND DISCHARGE OF BULK ABRASIVE PRODUCTS. SUGAR, FLOUR, MILK POWDER, GRANULATES ETC).

SEELE : WEISS, SCHADSTOFFFREI, ABRIEBFEST, NATURKAUMMI
EINLAGE : HOCHZUGFESTE SYNTHETISCHE TEXTILEINLAGE, EINE STAHLDRAHTSPIRALE UND ANTISTATISCHER KUPFERLITZE.
DECKE : OZON-UND WITTERUNGSBESTÄNDIGER, ABRIEBFESTER, SPEZIELLER SYNTHETISCHER GUMMI, GEPRÖCT.
ANWENDUNG : SAUG - DRUCKSCHLAUCH ZUR BEFÖRDERUNG VON ABRASIVEN MEDIEN WIE ZUCKER, MEHL, MILCHPULVER, GRANULATEN USW.

-40°C / + 80°C
-40°F / +176°F

İŞARETLEME / MARKING / BESCHRIFTUNG : TRANSFER TAPE OR EMBOSSED

WHITE - SDC | HEAVY DUTY BULK FOOD S.D HOSE W.P. 10 Bar. (145 PSI)

Normlar / Norms / Normen	ISO 1307	Renk / Colour / Farben	