

**UMF Concrete 37° Maximum Retraction**

UMF 30 Concrete 37° Steel

UMF 37°

**UMF 37°**

Article Part Number	Maximum Length Maximum Retraction		Reinforced Concrete	Rebar Diameter (mm)			
	Class	Size		16	18	20	22
UMF 30-30	UMF	8	UMF 30	17	18	3	14
UMF 30-30	UMF	8	UMF 30	18	18	4	14
UMF 30-30	UMF	8	UMF 30	20	18	4	17
UMF 30-30	UMF	8	UMF 30	18	18	4	18
UMF 30-30	UMF	8	UMF 30	20	18	5	17
UMF 30-30	UMF	8	UMF 30	20	18	5	18
UMF 30-30	UMF	8	UMF 30	20	18	5	20
UMF 30-30	UMF	8	UMF 30	20	18	5	22
UMF 30-30	UMF	10	UMF 30	20	18	5.5	18
UMF 30-30	UMF	10	UMF 30	20	18	5.5	20
UMF 30-30	UMF	10	UMF 30	20	18	5.5	22
UMF 30-30	UMF	10	UMF 30	27	18	5.5	27
UMF 30-30	UMF	12	UMF 30	20	18	5.5	24
UMF 30-30	UMF	12	UMF 30	18	18	5.5	27
UMF 30-30	UMF	12	UMF 30	20	18	5.5	30
UMF 30-30	UMF	15	UMF 30	18	18	11.5	27
UMF 30-30	UMF	15	UMF 30	20	18	11.5	30
UMF 30-30	UMF	20	UMF 30	20	18	14.5	30
UMF 30-30	UMF	20	UMF 30	20	18	14.5	33
UMF 30-30	UMF	20	UMF 30	20	18	14.5	36
UMF 30-30	UMF	20	UMF 30	20	18	14.5	40
UMF 30-30	UMF	20	UMF 30	20	18	14.5	45
UMF 30-30	UMF	20	UMF 30	20	18	14.5	50
UMF 30-30	UMF	20	UMF 30	20	18	14.5	55
UMF 30-30	UMF	20	UMF 30	20	18	14.5	60
UMF 30-30	UMF	20	UMF 30	20	18	14.5	75

UMF 30 Steel 37° Max Retraction



Reinforced Concrete  
 UMF 30 Concrete 37° Maximum Retraction  
 Maximum Length 3000 mm  
 Max. Weight 3.5 kg