OSDFC45F

Oil S&D 10 Bar
FLAT CORRUGATED

ID	OD	WP	BP	VACUUM	BRr	W	L
inch	mm	mm	bar	psi	bar	psi	bar	psi	mm	g/m	m
3/4"	19	29	10	150	30	450	-0,92	65	463	40-46-61
1"	25,4	36	10	150	30	450	-0,92	85	614	40-46-61
1 1/4"	32	43	10	150	30	450	-0,92	110	852	40-46-61
1 1/2"	38	49	10	150	30	450	-0,92	130	993	40-46-61
2"	50,8	63	10	150	30	450	-0,92	175	1499	40-46-61
2 1/2"	63,5	77	10	150	30	450	-0,92	210	2095	40-46-61
3"	76,2	90	10	150	30	450	-0,92	250	2571	40-46-61
4"	101,6	117	10	150	30	450	-0,92	360	3820	40-46-61
5"	127	145	10	150	30	450	-0,80	480	6190	40-46-61
6"	152,4	172	10	150	30	450	-0,80	600	8621	40-46-61
8"	203,2	225	10	150	30	450	-0,80	900	12425	30

SEÇENEKLER / OPTIONS / OPTIONEN

Talep Üzerine Tüp : İletken (D)
Tube Upon Request : Conductive (D)
Seele Nach Anfrage : Leitfähig (D)

TÜP : YAĞ VE BENZİNE DAYANIKLI SİYAH NBR.
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL, ÇELİK TEL HELİK VE ANTİSTATİK BAKIR TEL.
KAPAK : YAĞ, HAVA ŞARTLARI, OZON, AŞINMA VE DENİZ SUYUNA DAYANIKLI, DÜZ-OLUKLU, CİZİ, SENTETİK KAUÇUK.
UYGULAMA : %50'YE KADAR AROMATİK İÇERİĞİ OLAN PETROL ÜRÜNLERİNİN EMME VE BOŞALTOŞ İÇİN.

TUBE : OIL AND PETROL RESISTANT BLACK NBR.
REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE, STEEL WIRE HELIX AND ANTISTATIC COPPER WIRE.
COVER : OIL WEATHER, OZONE,ABRASION AND SEA WATER RESISTANT, FLAT-CORRUGATED, SPECIAL SYNTHETIC RUBBER
APPLICATION : FOR SUCTION AND DISCHARGE OF PETROLEUM PRODUCTS WITH AROMATIC CONTENT UP TO 50%.

SEELE : ÖL- UND KRAFTSTOFFBESTÄNDIG, NITRILGUMMI, SCHWARZ.
EINLAGE : HOCHZUGFESTE SYNTHETISCHE TEXTILEINLAGE, STAHLDRAHTSPIRALE UND ANTISTATISCHER KUPFERDRAHT.
DECKE : ÖL-,ZUSAMMENWITTERUNGSBESTÄNDIG, ABRIEBFEST, SPECIAL SYNTHETISCHER GUMMI, LEICHT GERILLT, GEEIGNET FÜR EINSATZ IM SALZHALTIGEN WASSER.
ANWENDUNG : SAUG- UND DRUCKSCHLAUCH FÜR MINERALÖLPRODUKTE MIT MAX. 50 % AROMATENGEHALT.

-30°C / + 70°C
-22°F / +158°F

ISARETLEME / MARKING / BESCHRIFTUNG : TRANSFER TAPE OR EMBOSSED

YAKIT FC / 10 **OIL S : D HOSE • W.P. 10 Bar (145 PSI)**

Normlar Norms Normen	ISO 1307	Renk Colour Farben	