Superelastic Medium Duty Suction&Delivery

CORRUGATED EXTERNAL HELIX (-30 °C)

TCS22

LAGINAC Series / LAGINA/C Series

ID		BP		VACUUM		BR/r		W		L	
inch	mm	bar	psi	mH_2O		mm		g/m		m	
3/4"	19	17	247	9		105		360		30/50	
1"	25	17	247	9		115		480		30/50	
	30	15	218	9		120		550		30/50	
1 1/4"	32	14	203	9		125		580		30/50	
	35	13	189	9		130		640		30/50	
1 1/2"	38	13	189	9		140		670		30/50	
	40	12	174	9		155		700		30/50	
	45	12	174	9		170		870		30/50	
2"	51	12	174	9		185		975		30/50	
	55	12	174	9		200		1080		30/50	
	60	12	174	9		220		1250		30/50	
2 1/2"	63	11	160	9		240		1350		30/50	
	70	9	131	9		250		1580		30/50	
3"	76	9	131	9		275		1700		30/50	
	80	9	131	9		285		1690		20/30	
	90	7	102	8		330		2100		20/30	
4"	102	7	102	8		365		2600		20/30	
	110	7	102	8		415		2900		20/30	
	120	7	102	7		490		3200		20/30	
5"	127	6	87	7		510		3650		20/30	
6"	152	6	87	7		605		5100		20/30	
8"	203	4	58	6		810		7850		10	

YAPI : KARABEL YÜKSEK EGRİMLİ, DÜZGÜN, SÜDÜK DAMARLI, SÜPER ELASTİK, PLASTİK ESTER/MİKS PVC.
KULLANIM ALANLARI : KİMYEVİ MADDE, KORROZİF, BALÇIK/DEMİR İNAL ESLARI, TAHVİL/ELEVATÖR, SON DERECE DAYANIKLI VE ESNEK, BAKIMSIZ VE AŞINMAYA DAYANIKLI, HAVA SARTLARINA VE KİMYASALLARA DAYANIKLI OLUKLU SÜRGÜLÜ TİPİ.
UYGULAMA : SERT, ESNEK VE PÜRÜZSÜZ, ÖZEL SÜPERELASTİK MALZEME, KORUGASYONLU, DIŞ KISMI SÜRGÜLÜ TİPİ.

CONSTRUCTION : STRONG, FLEXIBLE AND SMOOTH SPECIAL SUPERELASTIC MATERIAL.
SHOCK RESISTANT PVC SPIRAL.
CRUSHING, CHEMICAL AGENTS, ABRASION AND WEATHER RESISTANT, CORRUGATED SLIDING OUTSIDE.
APPLICATION : FOR MEDIUM DUTY SUCTION AND DELIVERY OF WATER, SALT WATER, LIGHT CHEMICALS, LIQUIDS ETC. IN AGRICOL TURAL, INDUSTRIAL APPLICATIONS,CONSTRUCTIONS, SEWER PURGING, SLUDGE, SLURRIES, WASTE MA TTER, SAND AND GRAVEL, ETC. ESPECIALLY FOR USE IN VERY COLD CLIMATES.

KONSTRUKTION : STABILER, HOCHFLEXIBLER, GLATTER, KALTERESISTENTER, SUPER ELASTISCHER, PLASTIFIZIERTER PVC.
MIT VERSTÄRKUNGSSPIRALE AUS SCHLAG-UND DRUCKFESTEM PVC.
ANWENDUNG : AUSSERST STRAPAZIERFÄHIG UND BIEGSAM, DRUCK-UND ABRIEBFEST, WITTERUNGS-UND CHEMIKALIENBESTÄNDIG, GEWELLTE GLEITEND AUSSENSCHICHT.
FÜR LEICHTE ANWENDUNGEN ZUR BE-UND ENTLADEN VON WASSER, SALZWASSER, LEICHTE CHEMIKALIEN, ABRASIVEN MEDIEN USW. FÜR LANDWIRTSCHAFT, INDUSTRIEN, BAUWERKE, IM HAUSHALT UND IN KANALISATIONEN, SPEZIELL ZUR VERWENDUNG IN EXTREM KALTEN GEBIETEN.

-30 °C / + 50 °C
-22 °F / +122 °F

İŞARETLEME / MARKING / BESCHRIFTUNG : INK - JET

LAGINA/C ... mm (month/year)

Normlar Norms Normen	ISO 1307	Renk Colour Farben	