FFC80F

Foodstuff S&D

FLAT-CORRUGATED UHMW-PE

RAKI SDFC-10 PE Serisi / RAKI SDFC-10 PE Series

ID		OD	WP		BP		VACUUM	BR/r	W	L
inch	mm	mm	bar	psi	bar	psi	bar	mm	g/m	m
3/4"	19	29	10	145	30	435	-0.92	70	480	40-46-61
1"	25.4	36	10	145	30	435	-0.92	90	625	40-46-61
1 1/4"	32	43	10	145	30	435	-0.92	130	910	40-46-61
1 1/2"	38	50	10	145	30	435	-0.92	180	1060	40-46-61
2"	50.8	64	10	145	30	435	-0.92	250	1525	40-46-61
2 1/2"	63.5	78	10	145	30	435	-0.92	280	2145	40-46-61
3"	76.2	91	10	145	30	435	-0.92	350	2550	40-46-61
4"	101.6	119	10	145	30	435	-0.92	450	4210	40-46-61
5"	127	148	10	145	30	435	-0.80	600	6475	40-46-61

Antma : Maks. 15 dakika boyunca 130 °c. buharlı, maks. 15 dakika boyunca 60 °c. kostik soda (%5) ile.
Sanification : Max. 130 °c for 15 min. with steam, max. 60 °c for 15 min. with caustic soda (5%).
Sterilisierung : Bei max. 130 °c für 15 min. mit dampf, bei max. 60 °c für15 min. mit natronlauge (5%).

TÜP : BEYAZ RENK TOKSİK OLMAYAN, TAT VE KOKU İÇERMEZ, UHMW-PE.
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL VE ÇELİK TEL HELEZON.
KAPAK : HAVA ŞARTLARINA, OZONA VE AŞINMAYA DAYANIKLI, ÖZEL SENTETİK KAUÇUK DÜZ-OLUKLU.
UYGULAMA : YÜKSEK ALKOL YÜZDELİ (99° KADAR) GIDA MADDELERİNİN EMME VE BOŞALTILMASI İÇİN. ÖZELLİKLE BİRA FABRİKALARINDA, İÇİM TESİSLERİNDE KULLANIM İÇİN.

TUBE : WHITE COLOUR NON - TOXIC, TASTE AND ODOUR FREE, UHMW-PE.
REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE AND STEEL WIRE HELIX.
COVER : WEATHER, OZONE AND ABRASION RESISTANT, SPECIAL SYNTHETIC RUBBER FLAT-CORRUGATED.
APPLICATION : FOR SUCTION AND DISCHARGE OF FOODSTUFF WITH HIGH PERCENTAGE OF ALCOHOL (UP TO 99). FOR USE SPECIALLY IN BREWERIES, DISTILLERIES.

SEELE : GESCHMACKS- UND GERUCHSNEUTRAL, WEISS, SCHADSTOFFFREI, UHMW-PE.
EINLAGE : HOCHZUGFESTE SYNTHETISCHE TEXTILEINLAGE MIT EINER STAHLDRAHTSPIRALE.
DECKE : OZON-UND WITTERUNGSBESTÄNDIGER, ABRIEBSFESTER, SPEZIELLER SYNTHETISCHER GUMMI, LEICHT GEWELL I
ANWENDUNG : SAUG - DRUCKSCHLAUCH FÜR FLÜSSIGKEITEN MIT HOHEM ALKOHOLANTEIL (BIS ZU 99 %) SPEZIELL FÜR BRAUEREIEN UND BRENNEREIEN.

-40°C / + 80°C
-40°F / +176°F

İŞARETLEME / MARKING / BESCHRIFTUNG : **TRANSFER TAPE OR EMBOSSED**

RAKI SDFC/10 PE — FOODSTUFF S/D HOSE • UHMW-PE • W.P. 10 Bar (145 PSİ)

Normlar Norms Normen	ISO 1307 MEETS FDA REQUIREMENTS	Renk Colour Farben	