Oil S&D 10 Bar
CORRUGATED

OC454

YAKIT SDC-10 Serisi / YAKIT SDC-10 Series

ID		OD	WP		BP		VACUUM	BR/r	W	L
inch	mm	mm	bar	psi	bar	psi	bar	mm	g/m	m
3/4"	19	29	10	145	30	435	-0.92	75	572	40-46-61
1"	25.4	35	10	145	30	435	-0.92	100	684	40-46-61
1 1/4"	32	42	10	145	30	435	-0.92	120	826	40-46-61
1 1/2"	38	48	10	145	30	435	-0.92	140	965	40-46-61
2"	50.8	63	10	145	30	435	-0.92	190	1697	40-46-61
2 1/2"	63.5	74	10	145	30	435	-0.92	250	1980	40-46-61
3"	76.2	89	10	145	30	435	-0.92	300	2670	40-46-61
4"	101.6	116	10	145	30	435	-0.92	425	3860	40-46-61
5"	127	145	10	145	30	435	-0.80	550	6035	40-46-61
6"	152.4	172	10	145	30	435	-0.80	640	7572	40-46-61

SEÇENEKLER / OPTIONS / OPTIONEN

Talep Üzerine Tüp : İletken (Ω)
Tube Upon Request : Conductive (Ω)
Seele Nach Anfrage : Leitfahig (Ω)

TÜP : YAĞ VE BENZİNE DAYANIKLI SİYAH NBR.
GÜÇLENDİRME : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL, ÇELİK TEL HELEKS VE ANTİSTATİK BAKIR TEL.
KAPAK : YAĞA, HAVA ŞARTLARINA, OZONA, AŞINMAYA VE DENİZ SUYUNA DAYANIKLI OLUKLU ÖZEL SENTETİK KAUÇUK.
UYGULAMA : %50'YE KADAR AROMATİK İÇERİĞİ OLAN PETROL ÜRÜNLERİNİN EMME VE TAHLİYESİ İÇİN.

TUBE : OIL AND PETROL RESISTANT BLACK NBR.
REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE, STEEL WIRE HELIX AND ANTISTATIC COPPER WIRE.
COVER : OIL, WEATHER, OZONE, ABRASION AND SEA WATER RESISTANT, CORRUGATED SPECIAL SYNTHETIC RUBBER.
APPLICATION : FOR SUCTION AND DISCHARGE OF PETROLEUM PRODUCTS WITH AROMATIC CONTENT UP TO 50%.

SEELE : ÖL- UND KRAFTSTOFFBESTANDIG, NITRILGUMMI, SCHWARZ.
EINLAGE : HOCHZUGFESTE SYNTHETISCHE TEXTILEINLAGE, STAHLDRAHTSPIRALE UND ANTISTATISCHER KUPFERLITZE.
DECKE : ÖL, OZON - UND WITTERUNGSBESTANDIG, ABRIEBFEST, SPEZIELL SYNTHETISCHER GUMMI, GEWELLT, GEEIGNET FÜR EINSATZ IM SALZHALTIGEN WASSER.
ANWENDUNG : SAUG UND DRUCKSCHLAUCH FÜR MINERALÖLPRODUKTE MIT MAX. 50 % AROMATENGEHALT.

-30˚C / + 70˚C
-22˚F / +158˚F

İŞARETLEME / MARKING / BESCHRIFTUNG : **TRANSFER TAPE OR EMBOSSED**

YAKIT SDC / 10 OIL S / D HOSE - W.P. 10 Bar (145 PSI)

Normlar Norms Normen	ISO 1307	Renk Colour Farben	