



TRIAM

Energy-Efficient Alternative to Cast-In-Place Concrete

TRIAM	6" (152.4 mm)		8" (203.2 mm)		10" (254 mm)		12" (304.8 mm)	
	TRIAM	TRIAM	TRIAM	TRIAM	TRIAM	TRIAM	TRIAM	TRIAM
Weight	2.5 lb/ft	3.5 lb/ft	4.5 lb/ft	5.5 lb/ft	6.5 lb/ft	7.5 lb/ft	8.5 lb/ft	9.5 lb/ft
Radius of Curvature	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft
Standard Length	10 ft	10 ft	10 ft	10 ft	10 ft	10 ft	10 ft	10 ft
Maximum Length	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft
Minimum Bend Radius	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft	12 ft
Typical Wall Thickness	0.075 in	0.075 in	0.075 in	0.075 in	0.075 in	0.075 in	0.075 in	0.075 in
Typical Internal Diameter	6.0 in	7.8 in	9.5 in	11.2 in	12.9 in	14.6 in	16.3 in	18.0 in
Typical External Diameter	6.7 in	8.5 in	10.2 in	11.9 in	13.6 in	15.3 in	17.0 in	18.7 in
Weight per Square Foot	2.5 lb/ft	3.5 lb/ft	4.5 lb/ft	5.5 lb/ft	6.5 lb/ft	7.5 lb/ft	8.5 lb/ft	9.5 lb/ft
Weight per Linear Foot	2.5 lb/ft	3.5 lb/ft	4.5 lb/ft	5.5 lb/ft	6.5 lb/ft	7.5 lb/ft	8.5 lb/ft	9.5 lb/ft

Advantages: • Lightweight • Easy to install


• Long Service Life • High Strength • Superior Thermal Insulation • Superior Sound Insulation

• Fast Installation • Superior Fire Resistance • Superior Durability

• No Seams • No Joints • Superior Weather Resistance • Superior Corrosion Resistance

 **Canada:** www.triamcanada.com
 1-800-551-1234 or 416-291-1234

 **United Kingdom:** www.triamuk.com
 +44 (0)151 488 4444

 **Germany:** www.triam.de
 +49 (0)30 800 000 000



TRIAM • 416-291-1234
 TRIAM • +44 (0)151 488 4444
 TRIAM • +49 (0)30 800 000 000

TRIAM is a registered trademark of TRIAM Corporation.

<p>TRIAM CORPORATION 1000 TRIAM DRIVE VICTOR, NY 14532</p>			
<p>USA 416-291-1234</p>	<p>UK +44 (0)151 488 4444</p>	<p>DE +49 (0)30 800 000 000</p>	<p>TR +90 (0)312 222 2222</p>